

Panel vision M

Panel vision L

Panel vision XL

Panel vision M 5.5 black **NEW**

Panel vision M 5.5 pure **NEW**



Panel vision M 5.5 style **NEW**

Panel vision L 5.5 pure **NEW**

Panel vision L 5.5 style **NEW**

Panel vision XL 5.0 pure

	Panel vision M 5.5 black NEW	Panel vision M 5.5 pure NEW	Panel vision M 5.5 style NEW	Panel vision L 5.5 pure NEW	Panel vision L 5.5 style NEW	Panel vision XL 5.0 pure
Power	From 465 Wp	From 465 Wp	From 465 Wp	From 515 Wp	From 515 Wp	From 610 Wp
Technology	Glass-glass	Glass-glass	Glass-glass	Glass-glass	Glass-glass	Glass-glass
Warranty	30 year performance 30 year product	30 year performance 30 year product	30 year performance 30 year product	30 year performance 25 year product	30 year performance 25 year product	30 year performance 15 year product
Properties	White reverse laminate Low CO ₂ footprint High Recycling Rate Black frame Black between cells Class A fire rating	Bifacial Low CO ₂ footprint High Recycling Rate Silver frame White between cells Class A fire rating	Bifacial Low CO ₂ footprint High Recycling Rate Black frame Transparent between cells Class A fire rating	Bifacial Low CO ₂ footprint High Recycling Rate Silver frame White between cells Class A fire rating	Bifacial Low CO ₂ footprint High Recycling Rate Black frame Transparent between cells Class A fire rating	Bifacial Low CO ₂ footprint High Recycling Rate Silver frame White between cells Class A fire rating
Cell Type	96 monocrystalline high power half-cut TOPCon solar cells	96 monocrystalline bifacial, high power half-cut TOPCon cells	96 monocrystalline bifacial, high power half-cut TOPCon cells	108 monocrystalline bifacial, high power half-cut TOPCon cells	108 monocrystalline bifacial, high power half-cut TOPCon cells	132 monocrystalline bifacial, high power half-cut TOPCon cells
Dimensions (mm)	1,762 x 1,134 x 35	1,762 x 1,134 x 35	1,762 x 1,134 x 35	1,977 x 1,134 x 35	1,977 x 1,134 x 35	2,382 x 1,134 x 30
Weight (kg)	24.8	24.8	24.8	27.6	27.6	33.4



Panel vision GM

Panel vision AM

Panel vision M

Panel vision GM 3.0 style

Panel vision AM 4.5 style

Panel vision M 5.0 black

Panel vision M 5.0 pure

Power	Up to 365 Wp	Up to 440 Wp	Up to 450 Wp	Up to 455 Wp
Technology	Glass-glass	Glass-glass	Glass-glass	Glass-glass
Warranty	30 year performance 30 year product	30 year performance 30 year product	30 year performance 30 year product	30 year performance 30 year product
Properties	Bifacial Black frame Transparent between cells Made in Germany with 100% renewable energy Cradle to Cradle Silver	Bifacial Black frame Transparent between cells Class A fire rating	Bifacial Low CO ₂ footprint High Recycling Rate Black frame Black between cells Class A fire rating	Bifacial Low CO ₂ footprint High Recycling Rate Silver frame White between cells Class A fire rating
Cell Type	120 monocrystalline bifacial, high power PERC-solar cells	Cell format M10 182mm TOPCon technology half-cut + multiwire	Cell format M10 182mm TOPCon technology half-cut + multiwire	Cell format M10 182mm TOPCon technology half-cut + multiwire
Dimensions (mm)	1,780 x 1,052 x 40	1,722 x 1,134 x 35	1,762 x 1,134 x 35	1,762 x 1,134 x 35
Weight (kg)	25.0~	24.0	24.8	24.8